



### Product Description

This product is a high-quality, eco-friendly light fixture with a slimmer design and an integrated driver. It has a length of 530mm, a width of 53mm, and a height of 94mm. The wattage varies from 20W to 50W. It features a high efficacy of 100lm/w and an opal polycarbonate diffuser. The beam angle is 120 degrees, and the Correlated Color Temperature (CCT) can be adjusted between 4000K, 5000K, and 6500K. The lumen output ranges from 3000lm to 4000lm. An optional PIR sensor is available for added functionality. This product is CE certified and has an IP65 rating, indicating it's dust-tight and protected against water projected from a nozzle.

### Lamp

Light Source	: <b>LED</b>
CRI	: <b>&gt;80</b>
Rated Life	: <b>50,000 HRs</b>
Wattage	: <b>20W   30W   40W   50W</b>
Beam Angle	: <b>120°</b>
CCT	: <b>4000K   5000K   65000K</b>

### Body

Color	: <b>White</b>
Material	: <b>Aluminum</b>
20W - L - W - H	: <b>630 - 63 - 63 MM</b>
30W - L - W - H	: <b>1204 - 76 - 94 MM</b>
40W - L - W - H	: <b>1204 - 76 - 94 MM</b>
50W - L - W - H	: <b>1504 - 76 - 94 MM</b>

### Electric

Control Gear	: <b>INTEGRATED</b>
Voltage	: <b>220 - 240V/50-60Hz</b>
Luminaire Efficacy	: <b>100 lm/W</b>
Inrush Current/ IC Duration	: <b>18A/ 250 µs</b>
Power Factor	: <b>0,9</b>
Ripple Current/ Flicker	: <b>10%</b>

### Other

Protection	: <b>IP65</b>
Safety Marks	: <b>Class I</b>
Impact Resistance	: <b>IK06</b>
Diffuser	: <b>Opal Poly carbonate</b>
Optional	: <b>PIR Sensor</b>

# TRI PROOF SERIES

Application Picture

*Lightronic*

Hall | Residencance | School | Colleges | Industrial Areas

