

Product Description

Recessed LED downlight to fulfill highest demands. Housing: die-cast aluminium constructed as heat sink. Bezel ring: die-cast aluminium, powdercoated. Shockproof cover made of plastic (opal). Luminaire also maintains the high protection type inside the false ceiling. Installation without tools thanks to spring fastening system. . Through-wiring box (5 pole) available as accessory. Ball impact proof in accordance with DIN 18032-03. Qualified for use in the food and drink industry.


Lamp

Light Source	: EPISTAR
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 5W 9W 12W 20W 30W
Beam Angle	: 110°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: White
Material	: Die-cast aluminum
5W Dia - H - Cut out	: 108 - 31 - 80
9W Dia - H - Cut out	: 138 - 32 - 115
12W Dia - H - Cut out	: 178 - 36 - 155
20W Dia - H - Cut out	: 188 - 36 - 160
30W Dia - H - Cut out	: 240 - 40 - 210

Electric

Control Gear	: TRIDONIC  PHILIPS
Input Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 100 lm/W
Output Current	: Constant Current
Output Voltage	: SELV

Other

Protection	: IP40
------------	--------

Option

Dimmable Option	: Triac 0/1 - 10V Dali
	: Wireless
Emergency Backup	: Battery Backup

Hall | Residence | School | Colleges

