

Product Description

LED Track-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. High quality converter without flickering and stroboscopic effect. With optional adapter for 3-circuit DALI tracks. Suitable for Track on ceiling, Wall track. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers.


Lamp

Light Source	: CREE ⇄ LED
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 30W 40W
Beam Angle	: 41°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: Black White
Material	: Die cast aluminium
Diameter (D)	: 105mm
Height (H)	: 120mm

Electric

Control Gear	: TRIDONIC  PHILIPS
Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 120 lm/W
Output Current	: Constant Current
Output Voltage	: SELV

Other

Protection	: IP20
Safety Marks	: IK06

Options

Dimmable Option	: Triac 0/1 - 10V Dali
	: Wireless

Hall | Residencance | School | Colleges | Commercial | Hospitality

