





# **Product Description**

Recessed LED downlight featuring advanced technology and sophisticated design. Housing: die-cast aluminium constructed as heat sink. Bezel ring: die-cast aluminium, powder coated. Open version. Highly polished four-segment faceted aluminium reflector with light mixing chamber. Installation without tools thanks to spring fastening system. Connected converter included in separate gearbox. With connecting cable . Suitable for through-wiring.

# Lamp

Light Source	:CREE\$ LED
CRI	:>90
Rated Life	: 50,000 HRs
Wattage	: 30W   40W
Beam Angle	: 50°
ССТ	: 2700K   3000K   4000K   6500K

### Body

Color	:White
Material	: Aluminum
20W-30W Dia (D) - SC (Ø) - H (mm)	: 125 - 115 - 115
30W-40W Dia (D) - SC (Ø) - H (mm)	: 160 - 134 - 157

#### Electric

Control Gear	:TRIDONIC VA PHILIPS	
Input Voltage	: 220 - 240V/50-60Hz	
Luminaire Efficacy	: 110 lm	
Output Current	: Constant Current	
Output Voltage	: SELV	
Other Protection	: IP 44	
Options		
Dimmable Option	: Triac  0/1 - 10V   Dali	
	Wireless	
Emergency Backup	: Battery Backup	



# Hall | Residence | School | Colleges

