



Product Description

LED surface-mounted projector in modern design with no visible cooling ribs. Housing: die-cast aluminium, powder-coated. Rotation range: 356°. Swivel range: 90°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with reflector made of MIRO-Silver with 98% total light reflection for outstanding efficiency - can be changed without tools. Best colour rendering index Ra>90. With multi adaptor for 3-circuit tracks 230V. Suitable for Track on ceiling, Wall track. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, decorative glasses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring.

Lamp

Light Source	: CREE LED
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 15W 20W 30W
Beam Angle	: 18° 36°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: Deep Matte Black
Material	: Die cast aluminum
10W Dia - H (mm)	: 53 - 125
20W Dia - H (mm)	: 75 - 190
30W Dia - H (mm)	: 75 - 190

Electric

Control Gear	: TRIDONIC VS
Input Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 120 lm/W
Output Current	: Constant Current
Output Voltage	: SELV

Other

Protection	: IP40
------------	--------

Other

Dimmable Option	: Triac 0/1 - 10V Dali Wireless
-----------------	---------------------------------------

Hall | Residence | School | Colleges

