



Product Description

Projector unit for tool-free mounting in separate recessed frame. Luminaire top: die-cast aluminium, powder-coated. Rotation range 356° and swivel range $\pm 35^\circ$. Inner cover prevents view into the false ceiling. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - Single, Double and Tripple options . Including separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Through-wiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Modular design.

Lamp

Light Source	: CREE ⇄ LED
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 2 x 35W
Beam Angle	: 60°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: Black/White
Material	: Aluminum
Length (L)	: 290 mm
Width (B)	: 150 mm
Height (H)	: 140 mm
Surface cut out Length	: 280 mm
Surface cut out width	: 140 mm

Electric

Control Gear	: TRIDONIC  PHILIPS
Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 110 lm/W
Output Current	: Constant Current
Output Voltag	: SELV

Other

Protection	: IP40
------------	--------

Options

Dimmable Option	: TRIAC 0/1 - 10V DALI
	: WIRELESS
Emergency Backup	: BATTERY BACKUP
	: CBS AC/DC

Hall | Residence | School | Colleges

