



Product Description

Cylindrical surface-mounted downlight. Housing: die-cast aluminium, powder-coated. Internal ceiling frame polycarbonate with bayonet mounting. Black/White plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. UVA- and IR-free light. Suitable for Ceiling

Lamp

Light Source	: CREE  LED
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 10W 20W 25W 30W 40W
Beam Angle	: 45°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: White / Black
Material	: Die cast aluminum
10W Dia - H	: 90 - 90
20W Dia - H	: 110 - 122
25W Dia - H	: 135 - 150
30W Dia - H	: 170 - 184
40W Dia - H	: 195 - 192

Electric

Control Gear	: TRIDONIC  PHILIPS
Input Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 115 lm/W
Output Current	: Constant Current
Output Voltage	: SELV

Other

Protection	: IP40
Impact Resistance	: IK06

Options

Dimmable Option	: Triac 0/1 - 10V Dali Wireless
-----------------	--

Hall | Residence | School | Commercial Area

