



Product Description

This high-performance, recessed LED downlight features a durable aluminum body with a clean white finish, designed to integrate seamlessly into modern architectural spaces. Engineered for versatility, it is available in multiple wattages ranging from 5W to 30W, delivering a broad 110° beam angle and an impressive luminaire efficacy of 100Lm/W. We offer complete flexibility in lighting design with a selectable color temperature range from 2700K to 6500K and an exceptional color rendering index of CRI >90 for superior vibrant color accuracy. The fixture provides smooth control across various environments with diverse dimming options, including Triac, 0-10V, and Dali systems. Built for long-term reliability, it operates efficiently on standard AC 220-240V voltage and boasts an extended rated life of up to 50,000 hours with IP40 ingress protection.

Light

Light Source	: LED
CRI	: >90
Wattage	: 5W 12W 20W 30W
Beam Angle	: 110°
Color Temperature	: 2700K 3000K 4000K 6500K
Rated Life	: 50,000 Hrs.

Body

Finish	: White
Material	: Aluminium
5W Diameter - Height - Cutout	: 108mm-31mm-80mm
12W Diameter - Height - Cutout	: 178mm-36mm-155mm
20W Diameter - Height - Cutout	: 188mm-36mm-160mm
30W Diameter - Height - Cutout	: 240mm-40mm-210mm

Electric

Voltage	: AC 220-240V
Fixture Lumen	: 500Lm-3000Lm
Luminaire Efficacy	: 100Lm/W

More informations

Dimming Option	: Triac 0-10V Dali
Ingress Protection	: IP40
Installation Type	: Recessed

