

IP 69K

IK 08



Product Description

This is a professional tubular light featuring a classic all-rounder design. It is engineered to provide optimal lighting solutions for a wide range of demanding applications, including train stations, airports, food and beverage industries, farms, cold storage facilities, and other harsh environments. Demonstrating high protection levels of IP69K and IK10, this light offers stable performance due to its robust construction utilizing PC, PMMA, tempered glass, and PE materials. Its design ensures reliability in challenging conditions.

Lamp

CRI	: 80 90 95
Rated Life	: 10,0000 HRs
Wattage (Adjustable)	: 20W 36W 48W
Beam Angle	: 1200
CCT	: 3000K 4000K 5000K 6500K

Body

Color	: White
Material	: Extruded PC, PMMA, PE , Glass, Stailness Steel
Length	: 600 mm 1200 mm 1500 mm
Diameter	: 70 mm

Electric

Voltage	: AC 220~240V ; DC 180 - 264V 50/60 Hz
Luminous Flux	: 3200LM 5760LM 7680LM
Luminous Efficacy	: 160 LM/W

Other

Ingress Protection (IP)	: IP69K
Impact Resistance (IK)	: IK08
Ambient Temperature	: -20~400 C

Options

Dimmable Option	: 1~10V DIM DALI Motion Sensor
-----------------	------------------------------------

