



We offer this versatile architectural lighting solution in both 30W and 40W configurations, delivering high-performance outputs ranging from 3300lm to 4400lm. Powered by an advanced CREE LED light source, it ensures exceptional color clarity with a high CRI of over 90 and a precise 50° beam angle. To perfectly suit any commercial or residential ambiance, the fixture supports multiple color temperatures ranging from a warm 2700K to a crisp 6500K, alongside flexible Triac, 0-10V, and Dali dimming options. Designed with an IP20 protection rating and a dependable rated lifespan of 20,000 hours, these downlights provide highly efficient, long-lasting illumination with an impressive efficacy of 110 Lm/W.

Light

Light Source	: 
CRI	: >90
Wattage	: 30W 40W
Beam Angle	: 50°
Color Temperature	: 2700K 3000K 4000K 5000K 6500K
Rated Life	: 20,000 Hrs.

Body

Finish	: White
Material	: Aluminium
Diameter (mm)	: 125mm 151mm
Cutout (mm)	: 115mm 140mm
Height (mm)	: 110mm 128mm

Electric

Voltage	: AC 220-240V
Fixture Lumen	: 3300lm - 4400lm
Luminaire Efficacy	: 110Lm/W

More informations

Dimming Option	: Triac 0-10V Dali
Ingress Protection	: IP20
Installation Type	: Recessed

