


LINEAR LIGHT LLT 6535R

Recessed Linear Light

Lightronic®



Product Description

Linear recessed ceiling and wall luminaire for aesthetically sophisticated lighting. Housing: extruded aluminium profile, powder-coated. End cap aluminium powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Ceiling mounting with pre-assembled SBS clamping bracket system. Suitable for Recessed ceiling mounting, Wall (recessed). LED unit with integrated converter interchangeable and removable. With sensors or as a safety luminaire on request.

Lamp

Light Source	: Tridonic LLE Module
CRI	: >85
Rated Life	: 50,000 HRs
Wattage	: 18W 26W 40W
Beam Angle	: 110°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: White Black Silver
Material	: Aluminum
Length (L)	: 1120 MM
Width (B)	: 65 MM
Height (H)	: 35 MM

Body color and size customization available

Electric

Control Gear	: TRIDONIC VS
Input Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 140 lm/W
Output Current	: Constant Current
Output Voltage	: SELV

Other

Protection	: IP40
------------	--------

Options

Dimmable Option	: 0/1 - 10V Dali
	: Wireless
Emergency Backup	: Battery Backup CBS AC/DC

LINEAR LIGHT LLT 6535R

Application Picture

Lightronic[®]

Hall | Residence | School | Colleges

