



Product Description

Recessed LED downlight featuring advanced technology and sophisticated design. Housing: die-cast aluminium constructed as heat sink. Bezel ring: die-cast aluminium, powder coated. Open version. Highly polished four-segment faceted aluminium reflector with light mixing chamber. Installation without tools thanks to spring fastening system. Connected converter included in separate gearbox. With connecting cable . Suitable for through-wiring.

Lamp

Light Source	: CREE LED
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 30W 40W
Beam Angle	: 50°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: White
Material	: Aluminum
30W Dia (D) - SC (Ø) - H (mm)	: 125 - 115 - 110
40W Dia (D) - SC (Ø) - H (mm)	: 151 - 140 - 128

Electric

Control Gear	: VS PHILIPS
Input Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 110 lm/w
Output Current	: Constant Current
Output Voltage	: SELV

Other

Protection	: IP 44
------------	---------

Options

Dimmable Option	: Triac 0/1 - 10V Dali
	: Wireless
Emergency Backup	: Battery Backup

Hall | Residence | School | Colleges

