


40w



50w

## Product Description

This technical specification sheet outlines the high-performance details for an LED luminaire, featuring a high-quality CREE LED light source with a CRI >90 for superior color accuracy. The product is powered by reliable Philips or VS control gear, operating on a standard 220-240V input while maintaining an impressive luminaire efficacy of 119 lm/W. Physical configurations are available in both 40W and 50W aluminum body options, with dimensions tailored for specific installation requirements. Users can select from a wide range of correlated color temperatures (CCT) spanning from warm 2700K to cool 6500K, all delivered at a precise 36° beam angle. Finally, the fixture offers robust versatility with an IP40 protection rating and multiple dimming options, including Triac, 1-10V, Dali, and Wireless controls.

## Lamp

Light Source	: <b>CREE</b> LED
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 40W - 50W
Beam Angle	: 36°
CCT	: 2700K   3000K   4000K   5000K   6500K

## Body

Color	: White
Material	: Aluminum
40W Dia (D) - C (Ø) - H (mm)	: 165 -125 - 155
50W Dia (D) - C (Ø) - H (mm)	: 195 - 175 - 144

## Electric

Control Gear	: <b>VS PHILIPS</b>
Input Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 119 lm
Output Current	: Constant Current
Output Voltage	: SELV

## Other

Protection	: IP40
------------	--------

## Options

Dimmable Option	: Triac   0/1 - 10V   Dali
	: Wireless

Hall | Residence | School | Colleges | Reatails | Showrooms

