



Product Description

Recessed projectors Housing: die-cast aluminium, powder-coated. Rotation range: 356°; swivel range: ± 35°. ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Installation without tools thanks to spring fastening system. Including separate LED converter with connecting cable . High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable, honeycomb louvre, clear and frosted diffusers.

Lamp

Light Source	: CREE ⇄ LED
CRI	: >90
Rated Life	: 50,000 HRs
Wattage	: 40W
Beam Angle	: 40°
CCT	: 2700K 3000K 4000K 6500K

Body

Color	: White
Material	: Die-cast Aluminum
Diameter (D)	: 160 mm
Height (H)	: 120 mm
Surface Cutout (ø)	: 145 mm

Electric

Control Gear	: TRIDONIC VS PHILIPS
Input Voltage	: 220 - 240V/50-60Hz
Luminaire Efficacy	: 100 lm/W
Output Current	: Constant Current
Output Voltage	: SELV

Other

Protection	: IP40
------------	--------

Options

Dimmable Option	: Triac 0/1 - 10V Dali Wireless
Emergency Backup	: Battery Backup CBS AC/DC

Hall | Residence | School | Retails | Showrooms

