



Product Description

This versatile LED lighting fixture is available in both suspended and surface-mounted configurations, featuring a sleek circular design in black or white finishes. Constructed from durable die-cast aluminum with a PMMA diffuser, the unit provides a broad 107° beam angle for consistent, glare-free illumination. You can choose from three distinct sizes—360 mm, 480 mm, or 600 mm in diameter—with power options ranging from 24W to 48W. The technical specifications highlight a crisp 4000K color temperature and high efficiency, reaching up to 96 lm/W for the largest model. To suit various installation needs, the fixture offers multiple driver options including non-dimmable, 0/1-10V, and DALI systems.

Lamp

Light Source	: LED
CRI	: >80
Wattage	: 42W
Beam Angle	: 107°
CCT	: 4000K
Power Factor	: >0.9

Body

Color	: Black White
Diffuser Material	: PMMA
Material	: Die Cast Aluminum
24W Diameter - Height	: 360 mm - 90 mm
30W Diameter - Height	: 480 mm - 90 mm
48W Diameter - Height	: 600 mm - 90 mm

Electric

24W Lumen at 4000K	: 2000lm
30W Lumen at 4000K	: 2800lm
48W Lumen at 4000K	: 4600lm
24W Efficiency at 4000K	: 83 lm/W
30W Efficiency at 4000K	: 93 lm/W
48W Efficiency at 4000K	: 96 lm/W

Other

Protection	: IP20
------------	--------

Other

Driver Option	: Non dimmable, 0/1 - 10V , Dali.
---------------	--------------------------------------

ZIFRA

Pendant Light

Lightronic[®]



