



Product Description

Powered by an efficient CREE LED chip, this fixture features a compact die-cast aluminum body with a clean white finish. It operates on an AC 220–240V voltage range and offers selectable wattages of 10W, 12W, or 15W, delivering a fixture lumen output of 1725 lm with a stellar efficacy of 115 lm/W. To meet diverse design needs, we provide flexible options including three beam angles (15°, 24°, or 36°) and five color temperatures ranging from 2700K to 5000K, all maintaining a high color rendering index of CRI >90. Finally, with a robust rated lifespan of 30,000 hours, an IP65 ingress protection rating, and support for Triac, 0–10V, and DALI dimming systems, this luminaire ensures both enduring reliability and precise control.

Light

Light Source	: CREE LED
CRI	: >90
Wattage	: 10W 12W 15W
Beam Angle	: 15° 24° 36°
Color Temperature	: 2700K 3000K 3500K 4000K 5000K
Rated Life	: 30,000 Hrs.

Body

Finish	: White
Material	: Die Cast Aluminium
Diameter (mm)	: 82mm
Cutout (mm)	: 75 mm
Height (mm)	: 60 mm

Electric

Voltage	: AC 220–240V
Fixture Lumen	: 1725lm
Luminaire Efficacy	: 115Lm/W

More informations

Dimming Option	: Triac 0–10V Dali
Ingress Protection	: IP65
Installation Type	: Recessed

COSMO

Recessed Spotlight

Lightronic[®]

