

IP20




Tilttable



Frame

Frame + Module

Full Fitting



Product Description

This luminaire features a high-grade aluminium body with a 90mm diameter and 68mm cutout size, available in white, black, or silver finishes. Powered by a high-quality Luminus LED source with a high CRI >90, it operates at 36VDC across wattage options of 6W, 8W, and 13W. The fixture produces an output ranging from 320Lm to 1050Lm at an efficacy of 80Lm/W, backed by a rated lifespan of 30,000 hours. We offer broad optical flexibility with beam angles of 15°, 24°, 38°, and 60°, alongside color temperatures spanning from 2700K to 6000K. Designed for indoor applications with an IP20 rating, it supports Triac, 0-10V, and DALI dimming options across operating temperatures from -20°C to 40°C.

Light

Light Source	: 
CRI	: >90
Wattage	: 6W 8W 13W
Beam Angle	: 15° 24° 38° 60°
Color Temperature	: 2700K 3000K 4000K
	5000K 6000K
Rated Life	: 30,000 Hrs.

Body

Finish	: White Black Silver
Material	: Aluminium
Diameter (mm)	: 90mm
Cutout (mm)	: 68mm
Height (mm)	: 35mm 70mm 80mm

Electric

Voltage	: 36VDC
Luminaire Efficacy	: 80Lm/W
Fixture Lumen Range	: 320Lm-1050Lm
Drive Current 6W	: 140mA
Drive Current 8W	: 180mA
Drive Current 13W	: 300mA

More informations

Operating Temperature	: -20°C ~ 40°C
Dimming Option	: Triac 0-10V Dali
Ingress Protection	: IP20

SEETO RD.

Spotlight

Lightronic®

IP20

Tilttable

