

IP20




Tiltable



Frame

Frame + Module

Full Fitting



Product Description

This Tiltable spotlight features an LED source with a high CRI of over 90, Wattages 6W, 8W & 13W, with a 38-degree beam angle. The physical build is detailed in the Body section, showcasing an aluminum material with white, black, or silver finish options, a 90mm width, and varied heights. Light operates on an AC 220-240V voltage range, producing a fixture lumen output between 480Lm and 1050Lm at an efficacy of 80Lm/W. Finally, the supplementary details include Triac, 0-10V, and Dali dimming options alongside an IP20 ingress protection rating.

Light

Light Source	: LED
CRI	: >90
Wattage	: 6W 8W 13W
Beam Angle	: 38°
Color Temperature	: 2700K 3000K 4000K
Rated Life	: 30,000 Hrs.

Body

Finish	: White Black Silver
Material	: Aluminium
Diameter (mm)	: 90mm
Cutout (mm)	: 68mm
Height (mm)	: 35mm 70mm 80mm

Electric

Voltage	: AC 220-240V
Fixture Lumen Range	: 480Lm-1050Lm
Luminaire E f cacy	: 80Lm/W

More informations

Dimming Option	: Triac 0-10V Dali
Ingress Protection	: IP20

SEETO RD.

Spotlight

Lightronic®

IP20

Tilttable

