

IP20

Tiltable






Frame



Frame + Module



Full Fitting



Product Description

Powered by a high-efficiency LUMINUS LED light source operating at 36VDC, this fixture is available in 6W, 8W, and 13W options delivering up to 1050 lumens at an efficacy of 80 Lm/W. It features high color accuracy with a CRI >90, offering color temperatures from 2700K to 6000K and beam angles of 15°, 24°, 38°, and 60°. Crafted from durable aluminum in white or black finishes, the fixture features a 90mm diameter, a 75mm cutout, and variable heights of 65mm, 100mm, or 110mm. For seamless lighting control, it supports Triac, 0-10V, and DALI dimming options. Rated IP20 for indoor environments, the luminaire operates reliably between -20°C and 40°C with an expected lifespan of 30,000 hours.

Light

Light Source	: 
CRI	: >90
Wattage	: 6W 8W 13W
Beam Angle	: 15° 24° 38° 60°
Color Temperature	: 2700K 3000K 4000K
	5000K 6000K
Rated Life	: 30,000 Hrs.

Body

Finish	: White Black
Material	: Aluminium
Diameter (mm)	: 90mm
Cutout (mm)	: 75mm
Height (mm)	: 65mm 100mm 110mm

Electric

Voltage	: 36V DC
Luminaire Efficacy	: 80Lm/W
Fixture Lumen Range	: 320Lm-1050Lm
Drive Current 6W	: 140mA
Drive Current 8W	: 180mA
Drive Current 13W	: 300mA

More informations

Operating Temperature	: -20°C ~ 40°C
Dimming Option	: Triac 0-10V Dali
Ingress Protection	: IP20

IP20

Tiltable

CCT (K)	Lumen Output @CRI 95 (lm)		
	13W	8W	6W
Dim-to-warm (with 13W LED)	880	480	320
2700K	950	570	430
3000K	1000	600	450
4000K	1050	630	470

REFLECTOR OPTIONS



Wall Washer Reflector



Slot Hole Reflector



Pinhole Reflector



Wall Washer - Full Fitting



Pin Hole - Full Fitting



Slot Hole - Full Fitting

TEYLA RD.

Spotlight

Lightronic[®]

IP20

Tilttable

