



5 YEAR
WARRANTY

150
LM/W

IK08

IP65



Product Description

This high-performance parking garage light features a durable design with two mounting options: a direct surface mount and a pendant-style pole extension. It utilizes a specialized Fresnel lens that creates a bat-wing light distribution to ensure uniform brightness across wide areas. For superior efficiency, the fixture delivers a high output of 150 lumens per watt and includes power and CCT selectable settings to meet various lighting demands with a single SKU. The unit is built to withstand harsh environments, boasting an IK08 impact protection rating and an operational temperature range from -40°C up to 50°C. Maintenance is simplified through a tool-free terminal box access and a dust-free lamp body designed without heat fins to prevent debris accumulation. Advanced control is provided by a built-in bi-level dimming microwave sensor that detects motion to optimize energy savings. Users are further protected by a 5-year warranty, ensuring long-term reliability for demanding commercial applications. Most notably, the fixture offers a long operational lifespan, maintaining at least 70% of its original light output for 100,000 hours

Lamp

Wattage	: 40W 60W 70W
CCT	: 3000K 4000K 5000K
Beam Angle	: 160°
CRI	: 80

Body

Color	: White
Material	: Aluminium & PC
Diameter	: 290mm
Height	: 146mm


Electric

Voltage	: 120-277V
Luminaire Efficacy	: 150 lm/W
Lumen at 70W	: 10500 lm
Lumen at 60W	: 9000 lm
Lumen at 40W	: 6000 lm


Other

IP Rating	: IP 65
IK Rating	: IK 08
Dimmable Option	: 0/1 - 10V
Ambient temperature	: -40°C to 50°C.
Sensor	: MWS
Hold Time	: 1 Minute

Installation Options



Surface Mount



Pole Mount

Application Picture :

